

# Quality - PW900 (B6000) - 150cm wide

## **Description**

900gsm PVC coated panama weave polyester. This quality is produced with a high gloss finish and an acrylic lacquer applied to both sides. We can offer a cut service for this to 150cm wide, in lots of 2 x 58m rolls or 4 x 29m rolls.

### **Product Details**

- cturio			
Roll sizes (nominal)	150cm x 58m (Lots of 2)	150cm x 29m (lots of 4)	
Finish	Gloss with lacquer both sides		
The standard range of 300cm x 58m rolls are available for cutting to 150cm			
wide. The full quantity of material must be taken after slitting.			
Yellow (1001)	Blue (5003)	Green (6027)	
Tan (1003)	Blue (5004)	Green (6028)	
Yellow (1018)	Mid Blue (5007)	Brilliant Green (6036)	
Yellow (1021)	Blue (5020)	Brunswick Green (6037)	
Yellow (1024)	Ice Blue (5023)	Pea Green (6038)	
Yellow (1025)	Pacific Blue (5025)	Bottle Green (6039)	
Yellow (1059)	French Blue (5026)	Grey (7001)	
Cream (1622)	Blue (5027)	Old Ford Grey (7002)	
Devon Cream (1623)	Ultra Blue (5028)	Grey (7003)	
Truck Red (3001)	Bright Blue (5029)	Charcoal Grey (7024)	
Juniper Red (3002)	J.P. Blue (5030)	Silver Grey (7060)	
Red (3015)	Blue (5031)	Dove Grey (7071)	
Flame Red (3016)	Oxford Blue (5032)	Grey (7179)	
Maroon (3017)	Dark Blue (5033)	Grey (7244)	
Int. Orange (3018)	Blue (5061)	Metalic Silver (7500)	
Orange (3021)	Blue (5063)	Black (7999)	
Orange (3056)	Blue (5104)	Brown (8020)	
Dark Maroon (3057)	Aircraft Blue (5158)	White (9002)	
Red (3105)	Green (6001)	White (9013)	
Blue (5001)	Green (6002)		

For further information, please contactcfsales@lowsofdundee.co.ukT

Tel: 01382 229251



# Quality - PW900 (B6000) - 150cm wide

### **Technical Data**

Parameter	Result	Test Method
Base Cloth	Polyester	
Coating	Flexible PVC both sides	
Finish	Acrylic Lacquer Both	
	Sides	
Total Weight	900gsm	
Tensile Strength	Warp - 4,000 N/50mm	EN ISO 1421
	Weft - 4,000 N/50mm	
Tear Strength	Warp - 600 N	DIN 53363
	Weft - 500 N	
Coating Adhesion	100 N/50mm	DIN 53357
Temperature	-30 / +70 Deg C	DIN EN ISO 1876-2
Resistance		
Fire Behaviour	<100mm/min	ISO 3795

### **Additional Information**

This quality is available as standard in 300cm x 58m rolls in the colours listed. A colour matching service is also available subject to a minimum order quantity of 1,000m (3,000sqm)

All Technical Data is indicative.

Specification details are offered in good faith, but will not be accepted in matters of warranty.

#### For further information, please contact

cfsales@lowsofdundee.co.uk

Tel: 01382 229251