



Quality - PW900 (B6000)

Description

900gsm PVC Coated Polyester with Gloss and Lacquered Finish

900gsm PVC coated panama weave polyester. This quality is produced with a high gloss finish and an acrylic lacquer applied to both sides. Mainly used for fabricating side curtains for trucks or heavy weight tarpaulins where higher strength is required.

Product Details

| Roll sizes (nominal) | 300cm x 58m | 300cm x 30m |
|--|--|---|
| Finish | Gloss with lacquer both sides | |
| All colours available in 58m rolls as standard. Colours marked * also available in 30m rolls. | | |
| Yellow (1001)* Tan (1003) Yellow (1018)* Yellow (1021) Yellow (1024) Yellow (1025) Yellow (1059) Cream (1622) Devon Cream (1623) Truck Red (3001)* Juniper Red (3002) Red (3015) Flame Red (3016) Maroon (3017) Int. Orange (3018)* Orange (3021) Orange (3056) Dark Maroon (3057) Red (3105) Blue (5001) | Blue (5003) Blue (5004) Mid Blue (5007)* Blue (5020) Ice Blue (5023) Pacific Blue (5025) French Blue (5026)* Blue (5027) Ultra Blue (5028) Bright Blue (5029) J.P. Blue (5030) Blue (5031) Oxford Blue (5032)* Dark Blue (5033) Blue (5061) Blue (5063) Blue (5104) Aircraft Blue (5158) Green (6001)* Green (6002) | Green (6027) Green (6028) Brilliant Green (6036) Brunswick Green (6037)* Pea Green (6038) Bottle Green (6039)* Grey (7001) Old Ford Grey (7002) Grey (7003) Charcoal Grey (7024)* Silver Grey (7060) Dove Grey (7071) Grey (7179) Grey (7244) Metallic Silver (7500)* Black (7999)* Brown (8020) White (9002)* White (9013) |

For further information, please contact

cfsales@lowsofdundee.co.uk

Tel: 01382 229251



Quality - PW900 (B6000)

Technical Data

| Parameter | Result | Test Method |
|------------------------|--|-------------------|
| Base Cloth | Polyester | |
| Coating | Flexible PVC both sides | |
| Finish | Acrylic Lacquer Both Sides | |
| Total Weight | 900gsm | |
| Tensile Strength | Warp - 4,000 N/50mm Weft - 4,000 N/50mm | EN ISO 1421 |
| Tear Strength | Warp - 600 N Weft - 500 N | DIN 53363 |
| Coating Adhesion | 100 N/50mm | DIN 53357 |
| Temperature Resistance | -30 / +70 Deg C | DIN EN ISO 1876-2 |
| Fire Behaviour | <100mm/min | ISO 3795 |

Additional Information

This quality is also available in 320cm wide as standard in black (7999) and white (9002) for special order. 320cm can also be produced in any colour subject to an MOQ of 1,000LM.

PW900 can also be supplied in slit rolls to customer requirement providing that a full 300cm x 58m rolls is ordered when slit. Slitting is subject to an additional charge and lead time. Please contact us to discuss your requirements.

All Technical Data is indicative.

Specification details are offered in good faith, but will not be accepted in matters of warranty.

For further information, please contact

cfsales@lowsofdundee.co.uk

Tel: 01382 229251

