

Quality - B7675

Description

630gsm PVC/PES, Anti Static

B7675 is an anti static quality, primarily used for industrial and mining ducting, it is also used for covers where anti static is a requirement. This quality is only available in black due to the carbon content. Other colours of antistatic PVC can be produced using different anti static methods. Please contact us for more information and a quotation

Product Details

Roll sizes (nominal)	150cm x 65m
Finish	Matt with lacquer
Standard Colours	Black (7999)

Technical Data

Parameter	Result	Test Method
Base Cloth	Polyester	
Coating	Flexible PVC both sides	
Finish	Matt with lacquer	
Total Weight	630gsm	
Tensile Strength	Warp - 2,500 N/50mm Weft - 2,000 N/50mm	EN ISO 1421
Tear Strength	Warp - 270 N Weft - 270 N	DIN 53363
Coating Adhesion	90 N/50mm	EN ISO 2411
Temperature Resistance	-30 / +70 Deg C	DIN EN ISO 1876-2
Fire Behaviour	<100mm/min	ISO 3795
Surface Resistivity	<10E6 Ohm	DIN 54345 T1

Note - Due to the carbon content, this quality can NOT be HF welded

All Technical Data is indicative.

Specification details are offered in good faith, but will not be accepted in matters of warranty.

For further information, please contact

cfsales@lowsofdundee.co.uk

Tel: 01382 229251