

## Quality - Tape Farbic 420 FR

### Description

#### **420gsm Woven coated Polyethylene, FR**

Woven coated polyethylene materials have a high strength to weight ratio. The primary use for PE420FR is for semi permanent structures for applications such as warehousing. Polyethylene does not contain dioxins, plasticisers or chlorines and is much more easily recycled in comparison to PVC

### Product Details

Quality	Tape Fabric 420 FR
Roll sizes (nominal)	300cm x 100m
Finish	-
Standard Colours	White

### Technical Data

Quality	Tape Fabric 420 FR	
Base Cloth	HDPE	
Construction	8x8 TPI (3400D)	
Coating	LDPE	
Weight	400gsm	
Tensile Strength	2,150/1,875 N/5cm	ISO1421-1
Elongation	21/21 %	ISO1421-1
Tear Strength	340/325 N	ISO4647-1
Temperature Stability	-40/+80 Deg C	
UV Stability	1,000 Kly	
Fire Behaviour	B-S1,D0	EN 13501-1

All Technical Data is indicative.

Specification details are offered in good faith, but will not be accepted in matters of warranty.

**For further information, please contact**

[cfsales@lowsofdundee.co.uk](mailto:cfsales@lowsofdundee.co.uk)

Tel: 01382 229251

