

## Quality - B7170

### Description

#### **520gsm PVC coated Polyester, FR.**

B7170 is a PVC coated PES with a higher light transmission than standard white structure products. Commonly used in structures for garden centres and nurseries where more light is required, this has proved a popular new addition to our standard range.

### Product Details

Roll sizes (nominal)	300cm x 65m
Finish	Gloss with lacquer both sides
Standard Colours	Translucent (0001)

### Technical Data

Parameter	Result	Test Method
Base Cloth	Polyester	
Coating	Flexible PVC both sides	
Finish	Gloss with lacquer both sides	
Total Weight	520gsm	
Tensile Strength	Warp - 2,500 N/50mm Weft - 2,000 N/50mm	EN ISO 1421
Tear Strength	Warp - 250 N Weft - 200 N	DIN 53363
Coating Adhesion	60 N/50mm	DIN 53357
Temperature Resistance	-30 / +70 Deg C	DIN EN ISO 1876-2
Fire Behaviour	M2 B-s2,d0	NFP92507 EN 13501-1
Special Properties	ABUV	
Light Transmission	40%	

All Technical Data is indicative.

Specification details are offered in good faith, but will not be accepted in matters of warranty.

**For further information, please contact**

[cfsales@lowsofdundee.co.uk](mailto:cfsales@lowsofdundee.co.uk)

Tel: 01382 229251