



Quality - PW900/FR (B6134)

Description

900gsm PVC Coated Polyester, Gloss and Lacquered Finish, FR

900gsm PVC coated panama weave polyester. This quality is produced with a high gloss finish and an acrylic lacquer applied to both sides and FR additive. Used for a variety of applications such as high speed doors or industrial chaltarc

Product Details

Roll sizes (nominal)	300cm x 60m
Finish	Gloss with lacquer both sides
Standard Colours	White (9002) Yellow (1001) Red (3001) Orange (3018) Blue (5007) Green (6001) Grey (7071) Black (7999)

Technical Data

Parameter	Result	Test Method
Base Cloth	Polyester	
Coating	Flexible PVC both sides	
Finish	Acrylic Lacquer Both Sides	
Total Weight	900gsm	
Tensile Strength	Warp - 4,000 N/50mm Weft - 4,000 N/50mm	EN ISO 1421
Tear Strength	Warp - 580 N Weft - 500 N	DIN 53363
Coating Adhesion	100 N/50mm	DIN 53357
Temperature Resistance	-30 / +70 Deg C	DIN EN ISO 1876-2
Fire Behaviour	M2	NFP92507

All Technical Data is indicative.

Specification details are offered in good faith, but will not be accepted in matters of warranty.

For further information, please contact

cfsales@lowsofdundee.co.uk

Tel: 01382 229251