

Quality - PE600/FR/L & PE650/FR/L

Description

600gsm & 650gsm PVC Coated Polyester for Marquees and Structures

Both of these products are produced for us in Europe in 50m rolls as standard in the widths shown. These qualities can be produced in other colours and some other widths subject to production run orders.

Product Details

Roll sizes (nominal)	250cmx 50m	320cmx50m	250cmx50m	300cmx50m
Finish	Gloss and Lacquered both side			
Standard Colours	White (9002)			

Technical Data

Parameter	PE600/FR/L (B7189A)	PE650/FR/L (B8103A)
Base Cloth	HT Polyester	HT Polyester
Coating	Flexible PVC both sides	Flexible PVC Both sides
Total Weight	600gsm	650gsm
Tensile Strength	Warp - 2,500 N/50mm	Warp - 2,500 N/50mm
ENISO 1421-1	Weft - 2,000 N/50mm	Weft - 2,300 N/50mm
Tear Strength	Warp - 250 N	Warp - 250 N
DIN 53363	Weft - 200 N	Weft - 200 N
Coating Adhesion	100 N/50mm	100 N/50mm
DIN 53357		
Fire Behaviour	BS7837, M2 (NFP92507)	BS7837, M2 (NFP92507)
Special Properties	ABUV	ABUV

Lows of Dundee are one of the largest distributors of industrial textiles and accessories in the UK. Based in Dundee, and with an extensive warehouse in Blackburn, we are well placed to send shipments all over the UK. Lows of Dundee have developed partnerships with suppliers from a number of countries across the world so that we can offer continuity of quality and supply for our standard products. With our primary partner, SIOEN, we also offer technical solutions in PVC coated textiles, developing customer specific products for specialist applications. We also offer production runs of products with a colour matching service for both standard and non standard products, including options such as duo colour, blockout, FR, lacquering and many more.

All Technical Data is indicative.

Specification details are offered in good faith, but will not be accepted in matters of warranty.

For further information, please contact

cfsales@lowsofdundee.co.uk

Tel: 01382 229251