

## Quality - PW900/FR (B6134)

### Description

#### **900gsm PVC Coated Polyester, Gloss and Lacquered Finish, FR**

900gsm PVC coated panama weave polyester. This quality is produced with a high gloss finish and an acrylic lacquer applied to both sides and FR additive.

Used for a variety of applications such as high speed doors or industrial shelters.

### Product Details

|                      |  |
|----------------------|--|
| Roll sizes (nominal) | 300cm x 60m  |
| Finish               | Gloss with lacquer both sides  |
| Standard Colours     | White (9002)<br>Yellow (1001)<br>Red (3001)<br>Orange (3018)<br>Blue (5007)<br>Green (6001)<br>Grey (7071)<br>Black (7999) |

### Technical Data

| Parameter              | Result                                     | Test Method       |
|------------------------|--|-------------------|
| Base Cloth             | Polyester                                  |                   |
| Coating                | Flexible PVC both sides                    |                   |
| Finish                 | Acrylic Lacquer Both Sides                 |                   |
| Total Weight           | 900gsm                                     |                   |
| Tensile Strength       | Warp - 4,000 N/50mm<br>Weft - 4,000 N/50mm | EN ISO 1421       |
| Tear Strength          | Warp - 580 N<br>Weft - 500 N               | DIN 53363         |
| Coating Adhesion       | 100 N/50mm                                 | DIN 53357         |
| Temperature Resistance | -30 / +70 Deg C                            | DIN EN ISO 1876-2 |
| Fire Behaviour         | M2   | NFP92507          |

All Technical Data is indicative.

Specification details are offered in good faith, but will not be accepted in matters of warranty.

**For further information, please contact**

[cfsales@lowsofdundee.co.uk](mailto:cfsales@lowsofdundee.co.uk)

Tel: 01382 229251