

Quality - B6353

Description

1,450gsm Foam Backed PVC/PES

B6353 is available in 250cm on 50m rolls as standard in grey and white. Flame retardant (M2), this quality is used in applications where a greater degree of insulation is required. Thermal conductance figures are included in the specification. Accoustic insualtion figures are available on request.

Product Details

Roll sizes (nominal)	250cm x 50m
Finish	Gloss with lacquer face, foam back side
Standard Colours	White (9002) Grey (7024)

Technical Data

Parameter	Result	Test Method
Base Cloth	Polyester	
Coating	PVC Face, PVC Foam Back	
Finish	Acrylic Lacquer Both	
Total Weight	1,450gsm	
Tensile Strength	Warp - 4,000 N/50mm Weft - 3,500 N/50mm	EN ISO 1421
Tear Strength	Warp - 600 N Weft - 500 N	DIN 53363
Coating Adhesion	120 N/50mm	EN ISO 2411
Temperature Resistance	-30 / +70 Deg C	DIN EN ISO 1876-2
Fire Behaviour	M2	NFP92507
Thermal Conductance	$\leq 4 \text{ W/m}^2 \cdot \text{K}$	
Special Properties	ABUV	

All Technical Data is indicative.

Specification details are offered in good faith, but will not be accepted in matters of warranty.

For further information, please contact

cfsales@lowsofdundee.co.uk

Tel: 01382 229251