

## Qualities - B8103 & B7120

### Description

#### **650gsm & 550gsm PVC Coated Polyester, Gloss and Lacquered, FR**

B8103 and B7120 are both flame retardant PVC coated polyester materials used in the fabrication of tents, marquees and structures. B8103, at 650gsm, is the common specification used for marquee walling and roofing. B7120, at 550gsm, is more commonly used for smaller structures or walling.

### Product Details

Roll sizes (nominal)	250cm x 65m	300cm x 65m
Finish	Gloss and SIOFLUO Lacquer	
Standard Colours	Yellow (1021) Cream (1932) Red (3016) Blue (5007) Blue (5029) Green (6001) Grey (7001) Grey (7244) Silver (7500) Black (7999) White (9909)	White (9909)

### Technical Data

Parameter	B8103	B7120
Base Cloth	HT Polyester	HT Polyester
Coating	Flexible PVC both sides	Flexible PVC Both sides
Total Weight	650gsm	550gsm
Tensile Strength ENISO 1421-1	Warp - 2,500 N/50mm Weft - 2,300 N/50mm	Warp - 2,500 N/50mm Weft - 2,000 N/50mm
Tear Strength DIN 53363	Warp - 250 N Weft - 200 N	Warp - 250 N Weft - 200 N
Coating Adhesion DIN 53357	100 N/50mm	100 N/50mm
Fire Behaviour	BS7837, M2 (NFP92507)	BS7837, M2 (NFP92507)
Special Properties	ABUV	ABUV

All Technical Data is indicative.

Specification details are offered in good faith, but will not be accepted in matters of warranty.

**For further information, please contact**

[cfsales@lowsofdundee.co.uk](mailto:cfsales@lowsofdundee.co.uk)

Tel: 01382 229251

