



## Quality - PE600/FR/L & PE650/FR/L

### Description

#### **600gsm & 650gsm PVC Coated Polyester for Marquees and Structures**

Both of these products are produced for us in Europe in 50m rolls as standard in the widths shown. These qualities can be produced in other colours and some other widths subject to production run orders.

### Product Details

Roll sizes (nominal)	250cmx 50m	320cmx50m	250cmx50m	300cmx50m
Finish	Gloss and Lacquer			
Standard Colours	White (9002)			

### Technical Data

Parameter	PE600/FR/L (B7189A)	PE650/FR/L (B8197A)
Base Cloth	HT Polyester	HT Polyester
Coating	Flexible PVC both sides with Acylic	Flexible PVC both sides with SIOFLUO lacquer
Total Weight	600gsm	650gsm
Tensile Strength ENISO 1421-1	Warp - 2,500 N/50mm Weft - 2,000 N/50mm	Warp - 2,500 N/50mm Weft - 2,500 N/50mm
Tear Strength DIN 53363	Warp - 250 N Weft - 200 N	Warp - 250 N Weft - 200 N
Coating Adhesion ISO2411	100 N/50mm	100 N/50mm
Fire Behaviour	BS7837, M2 (NFP92507)	BS7837, M2 (NFP92507)
Special Properties	ABUV	ABUV

All Technical Data is indicative.

Specification details are offered in good faith, but will not be accepted in matters of warranty.

**For further information, please contact**

[cfsales@lowsofdundee.co.uk](mailto:cfsales@lowsofdundee.co.uk)

Tel: 01382 229251

