

Quality - B7170/FR

Description

520gsm PVC coated Polyester, FR

B7170 is a PVC coated PES with a higher light transmission than standard white structure products. Commonly used in structures for garden centres and nurseries where more light is required, this has proved a popular new addition to our standard range.

Product Details

Roll sizes (nominal)	300cm x 65m
Finish	Gloss with lacquer both sides
Standard Colours	Translucent (0001)

Technical Data

Parameter	Result	Test Method
Base Cloth	Polyester	
Coating	Flexible PVC both sides	
Finish	Gloss with lacquer	
Total Weight	520gsm	
Tensile Strength	Warp - 2,500 N/50mm Weft - 2,000 N/50mm	EN ISO 1421
Tear Strength	Warp - 250 N Weft - 200 N	DIN 53363
Coating Adhesion	60 N/50mm	DIN 53357
Temp Resistance	-30 / +70 Deg C	DIN EN ISO 1876-2
Fire Behaviour	M2, B-s2,d0	NFP92507 EN 13501-1
Special Properties	ABUV	
Light Transmission	40%	

All Technical Data is indicative.

Specification details are offered in good faith, but will not be accepted in matters of warranty.

For further information, please contact

cfsales@lowsofdundee.co.uk

Tel: 01382 229251