

## Quality - PE600/FR/L & PE650/FR/L

### Description

#### 600gsm & 650gsm PVC Coated Polyester for Marquees and Structures

Both of these products are produced for us in Europe in 50m rolls as standard in the widths shown. These qualities can be produced in other colours and some other widths subject to production run orders.

### Product Details

|                      |                               |           |           |           |
|----------------------|-------------------------------|-----------|-----------|-----------|
| Roll sizes (nominal) | 250cmx 50m                    | 320cmx50m | 250cmx50m | 300cmx50m |
| Finish               | Gloss and Lacquered both side |           |           |           |
| Standard Colours     | White (9002)                  |           |           |           |

### Technical Data

| Parameter                        | PE600/FR/L (B7189A)                        | PE650/FR/L (B8103A)                        |
|----------------------------------|--|--|
| Base Cloth                       | HT Polyester                               | HT Polyester                               |
| Coating                          | Flexible PVC both sides                    | Flexible PVC Both sides                    |
| Total Weight                     | 600gsm                                     | 650gsm                                     |
| Tensile Strength<br>ENISO 1421-1 | Warp - 2,500 N/50mm<br>Weft - 2,000 N/50mm | Warp - 2,500 N/50mm<br>Weft - 2,300 N/50mm |
| Tear Strength<br>DIN 53363       | Warp - 250 N<br>Weft - 200 N               | Warp - 270 N<br>Weft - 270 N               |
| Coating Adhesion<br>DIN 53357    | 100 N/50mm                                 | 100 N/50mm                                 |
| Fire Behaviour                   | BS7837, M2 (NFP92507)                      | BS7837, M2 (NFP92507)                      |
| Special Properties               | ABUV                                       | ABUV                                       |

**For further information, please contact**

[cfsales@lowsofdundee.co.uk](mailto:cfsales@lowsofdundee.co.uk)

Tel: 01382 229251