



Quality - PC400

Description

470gsm Blended Polyester/Cotton, FWR

A blended polyester/cotton with a finished weight of 470gsm. This quality has a rot and water resistant treatment as well as being flame retardant to BS7837. PC400 is produced with a dry finish to it to help reduce dust attraction.

Product Details

Roll sizes (nominal)	150cm x 50m	200cm x 50m
Standard Colours	White	White Sand Dark Olive

Technical Data

Parameter	Result	Test Method
Treatment	FWR	
Weave	Plain	
Total Weight	470gsm	
Tensile Strength	Warp - 2,100 N/50mm Weft - 1,600 N/50mm	AS 2001.2.3
Tear Strength	Warp - 90 N Weft - 55 N	AS2001.2.10
Rot Resistance	Pass	EN-ISO 846
Shrinkage Estimate	Approx. 3%	
Water Resistance	50cm HH	AS2001.2.17
Fire Behaviour	Pass	BS7837

NOTE - Polyester cotton is a partly natural product and can react differently from batch to batch in terms of shrinkage. It can also become more translucent when wet. This does not effect the mechanical properties or proofing level.

All Technical Data is indicative.

Specification details are offered in good faith, but will not be accepted in matters of warranty.

For further information, please contact

cfsales@lowsofdundee.co.uk

Tel: 01382 229251