



Quality - Regentex 12 Rip Stop, RW

Description

550gsm Proofed Polyester Cotton Blend, Rip Stop, RW

This quality is treated with a rot and water resistant proofing. It is produced using a rip stop weave to give an improved tear strength over plain weave products. It is used for covers and tarpaulins where a breathable material is required.

Product Details

Roll sizes (nominal)	183cm x 50m
Standard Colours	Green Blue Red

Technical Data

Parameter	Result	Test Method
Material	Polyester/Cotton, Rip stop	
Treatment	RW	
Total Weight	550gsm	
Tensile Strength	Warp - 1,800 N/50mm Weft - 1,300 N/50mm	BS EN ISO 13934-1
Wing Rip Tear Strength	Warp - 40 N Weft - 30 N	BE EN ISO 13937-3
Hydrostatic Head	40 cm	ISO 811
Estimated shrinkage	Up to 5%	
Fire Behaviour	-	-

NOTE - Polyester Cotton is a partially natural product and can react differently from batch to batch in terms of shrinkage. It can also become more translucent when wet. This does not effect the mechanical properties or proofing level.

All Technical Data is indicative.

Specification details are offered in good faith, but will not be accepted in matters of warranty.

For further information, please contact

cfsales@lowsofdundee.co.uk

Tel: 01382 229251