

**New Formulation PE600/ FR/ L & PE650/ FR/ L Marquee and
Structure Fabrics
Using Specially Selected Yarn & Woven Base Fabric**

SPECIFICATION

	<u>PE600/ FR/ L</u>	<u>PE650/ FR/ L</u>
Width	250/ 320cm	250/ 300cm
Fabric	100% PES, 1100 d/tex 7x7 Threads/cm	100% PES, 1100 d/tex 8x8 Threads/cm
Weight	600g/ m ²	650g/ m ²
Colours	White 9002	White 9002
Finish	Gloss and Laquered	Gloss Lacquered
Breaking Strength EN ISO 1421 - 1	Warp 2500 N/5cm Weft 2000 N/5cm	Warp 2500 N/5cm Weft 2300 N/5cm
Tear Strength DIN53 363	Warp 250 N Weft 200 N	Warp 270 N Weft 270 N
Coating Adhesion EN ISO 2411	100 N/5cm	100 N/5cm
Temperature Resistance DIN EN 1876 - 2	- 30/ + 70 ^o C	- 30/ + 70 ^o C
Special Properties	ABUV, Fire Behaviour M2 (NFP 92507) BS7837 : 1996	

Figures quoted are indicative.

Specification details are offered in good faith, but will not be accepted in matters of warranty.