

Qualities - PEL350/FR & PEL580 Laminated PVC/PES

Description

350gsm FR and 580gsm Laminated PVC/PES qualities

Laminated PVC qualities are a more economical coated product than standard spread coating. We have introduced a 350gsm FR quality and a 580gsm standard quality which have been used for static covers, screens and many other applications where it is appropriate.

Product Details

Quality	PEL350/FR	PEL580
Roll sizes (nominal)	203cm x 50m	205cm x 50m
Finish	Matt	
Standard Colours	Blue Green Black White Yellow Brown	Blue Green Black Grey

Technical Data

Quality	PEL350/FR	PEL580
Base Cloth	Polyester	Polyester
Coating	Flexible PVC both sides	Flexible PVC both sides
Total Weight	350gsm	580gsm
Tensile Strength	Warp - 600 N/50mm Weft - 550 N/50mm	Warp - 1,200 N/50mm Weft - 1,050 N/50mm
Tear Strength	Warp - 120 N Weft - 100 N	Warp - 200 N Weft - 200 N
Coating Adhesion	70 N/50mm	70 N/50mm
Fire Behaviour	BS7837:1996	

All Technical Data is indicative.

Specification details are offered in good faith, but will not be accepted in matters of warranty.

For further information, please contact

cfsales@lowsofdundee.co.uk

Tel: 01382 229251